

HELI
LIFTING THE FUTURE

25 YEARS

TOP1 FORKLIFT MANUFACTURER AND SALER
IN CHINA FOR CONSECUTIVE 25 YEARS

Load Curve



CDD10-070

1.0 Ton Electric Fork Over Stacker

Lifting Height: 2000-3300mm

Advantages

Configuration and Performance

- Separately excited motor, Strong climbing ability.
- High strength forks.
- Built-in charger.
- Automatic lifting limit, Motor and battery life extension.

Safety

- Stepless speed control system, safe and quiet.
- Controller with Multiple automatic protection
- Emergency reversing device/Emergency brake switch.

Built-in charger

Free-maintained battery

Integrated fork, much stronger

24 YEARS



TOP1 FORKLIFT MANUFACTURER AND SALER
IN CHINA FOR CONSECUTIVE 24 YEARS

Type	Lift height (mm)	Mast type	Outside width between legs (mm)	Inside width between legs (mm)
CDD10-070	2000/2500/3000/3300	Standard 2-STAGE	550/600/650/685	180/230/280/315

HELI CDD10-070

Feature			
Model			CDD10
Configuration No.			070
Type			Fork over
Mast type			Standard 2-Stage
Load capacity	kg		1000
Load center	mm		600
Wheel base	mm		1150
Operating type			Walkie
Wheels			
Wheels type			PU
Wheel quantity	Driving wheel/Balance wheel/Bearing wheel		1/1/4
Dimension			
Standard lift height	mm		2000/2500/3000/3300
Max.extend height	mm		2385/2885/3385/3685
Mast lowered height	mm		1550/1800/2050/2200
Lowered fork height	mm		90
Fork size(length/width/thickness)	mm		1150(1220)/185/55
Overall length	mm		1733
Overall width	mm		790
Outside width between forks	mm		550/600/650/685
Inside width between forks	mm		180/230/280/315
Min.Turning radius	mm		1350
Min.Aisle width for pallets 800×1200	mm		1914
Min.Aisle width for pallets 1000×1200	mm		1955
Min.ground clearance	mm		30
Performance			
Travel speed,laden/unladen	km/h		3/3.5
Lift speed,laden/unladen	mm/s		120/180
Lowering speed,laden/unladen	mm/s		120/120
Gradeability,laden/unladen	%		5/7
Electrical configuration			
Drive motor/Lift motor/Steering motor	kW		DC0.63/DC2.0
Battery voltage	V		24
Battery capacity	Ah		85
Brake			Electromagnetic/Regenerative
Controller			HELI(Options CURTIS)
Weight			
Battery weight	kg		52
Service weight with battery	kg		600

* Details of specifications and equipment are based on information available at time of printing and may change without notice.



ANHUI HELI CO., LTD.

ADD: NO.668 Fangxing Street,Economical Development Zone,Hefei,P.R.China
 TEL : (86 55 1)63639068,63639258,63639358,63662105,63639530
 FAX : (86 551)63639966
 WEBSITE : <http://www.helichina.net>
 Email : hel@helichina.net

AUTHORIZED DEALER